

22779 - GE LED HID - Type B

LED50ED23.5M/740

- ☞ Open and Closed Rated
- ☞ Ballast Bypass required
- ☞ Damp
- ☞ Not suitable for air-tight explosive or hazardous fixtures
- ☞ For additional collateral click the link below: https://products.currentbyge.com/led-lamps-and-modules/led-replacement-for-hid

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	Medium Screw
Base Type	Screw-In
Body Color	Clear
Dimmable	No
Primary Application	Replacement for HID
Product Color	Clear
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	17.1 yr
Requested Structure	Carton
Estimated Energy Cost per Year	16.06

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	150
Initial Lumens-nominal	7500 lm
Color Rendering Index-CRI	70
Color Temperature	4000 K

PRODUCT INFORMATION

Product Code	22779
Description	LED50ED23.5M/740
Alternative Unit Of Measure	CASE
Standard Package Quantity	3
Ean UPC	043168227797
Standard Package GTIN	10043168227794
No Of Items Per Sales Unit	
No Of Items Per Standard Package	3
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168227797
Standard Package GTIN	00043168227797
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	7.7 in
-----------------------------	--------

ELECTRICAL CHARACTERISTICS

Voltage <Nom>	120 V
Rated power (Watts)	50 W