

Catalog Number
Notes
Type

## FEATURES & SPECIFICATIONS

**INTENDED USE** — Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent. For use in light Industrial applications such as, warehousing and other large indoor spaces with mounting heights ranging from 10' – permitted. **Certain airborne contaminants can diminish integrity of acrylic and LED's.** [Click here for Acrylic Environmental Compatibility table for suitable uses.](#)

**Certain airborne contaminants may adversely affect the functioning of LEDs and other electronic components, depending on various factors such as concentrations of the contaminants, ventilation, and temperature at the end-user location.** [Click here for a list of substances that may not be suitable for interaction with LEDs and other electronic components.](#)

**CONSTRUCTION** — Solid aluminum channel enables superior thermal performance at warm ambient temperatures.

Acrylic Textured Clear (ATC) and semi-diffuse lens optional to provide glare control and LED protection.

**ELECTRICAL** — 70% lumen maintenance at >100,000 hours. Thermally protected driver standard with 0-10V dimming, 6kV/3kA surge protection is standard on MVOLT. 10kV/5kA surge protection is standard on HVOLT. Optional 10kV/5kA available on MVOLT. Surge protection is tested in accordance with IEEE/ANSI standards.

Luminaire surge protection level: Designed to with stand up to 6kV/3kA per ANSI C82.77-5-2015.

Luminaire surge protection level: Designed to with stand up to 10kV/5kA per ANSI C82.77-5-2015.

LSXR Sensor option provides increased energy savings.

**INSTALLATION** — Suitable for suspension by chain, cable, surface-mounting bracket, hook monopoint or single (pendant) monopoint. Surface mounting not recommended. 2" offset mounting can be accomplished with the optional THUN mounting bracket. To maintain ambient listing, fixture should be mounted at a minimum plenum height of 18".

**LISTINGS** — UL, CUL listed. Damp location listed. Listed for use in ambient operating temperatures from -40°C to 45°C. Thermal management system allows for safe operation during times when temperatures rise to 55°C\*.

DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at [www.designlights.org/QPL](http://www.designlights.org/QPL) to confirm which versions are qualified.



**WARRANTY** — 5-year limited warranty. Complete warranty terms located at: [www.acuitybrands.com/resources/terms-and-conditions](http://www.acuitybrands.com/resources/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.


LED High Bay

# I-BEAM® IBE


12,000 through 30,000 Lumens




A - 7/8" KNOCK OUT



IBE L24 LUMINAIRE



IBE L48 LUMINAIRE



IBE L48 LUMINAIRE

\*Prolonged use at 55°C may impact long-term performance.

# IBE LED High Bay

**CS** Looking for Contractor Select readily available configurations? Click here to visit Contractor Select™ spec sheet or go to [www.contractorselect.com](http://www.contractorselect.com)

**ORDERING INFORMATION** Lead times will vary depending on options selected. Consult with your sales representative. **Example:** IBE L24 18000LM ATC MD MVOLT GZ10 40K 80CRI DWH

IBE							MD			GZ10				
Series	Fixture length		Lumens		Lens		Distribution		Voltage		Driver		Color temperature	
IBE LED bay light	L24	24"	12000LM	12,000 lumens	ATC	Acrylic Textured semi-diffuse lens, .040" thick	MD	Medium	MVOLT	120-277V	GZ10	0-10V dimming	40K	4000 K
			15000LM	15,000 lumens			ND	Narrow	HVOLT	347V-480V <sup>3</sup>			50K	5000 K
			18000LM	18,000 lumens <sup>1</sup>					120	120V				
			22000LM	22,000 lumens <sup>1</sup>					208	208V				
	L48	48"	18000LM	18,000 lumens	L/LENS	Less lens <sup>2</sup>			240	240V				
			22000LM	22,000 lumens	SD080	Semi-Diffuse acrylic, .080" thick			277	277V				
			30000LM	30,000 lumens					347	347V <sup>4</sup>				
									480	480V <sup>4</sup>				

Color rendering index	Options										Finish		
80CRI 80 CRI	E15WCP	EM self-diagnostics battery pack, 5°C min., 15W, Certified in CA Title 20 MAEDBS <sup>4,6</sup>					<u>Motion sensors:</u>					DWH Gloss white	
	BPK	Fixture back pack (required with E15WCP)					LCOZU	Aisle motion sensor, pre-wired <sup>6,10</sup>					
	OUTCTR	Wiring leads pulled through back center of fixture (not available with back pack)					LCHOSZU	Aisle motion sensor, pre-wired; programmable dimming <sup>6,10</sup>					
	SPD	Surge protection device <sup>5</sup>					LCPZU	Aisle motion sensor with photocell; pre-wired <sup>6,10</sup>					
	OCS	RELOC® OnePass® 5' installed <sup>6</sup>					LAOZU	360° motion sensor, pre-wired <sup>6,10</sup>					
	RRL	RELOC®-ready luminaire. See page 5 for ordering information (must be ordered separately)					LAHOSZU	360° motion sensor, pre-wired; programmable dimming <sup>6,10</sup>					
	IMP	Integrated modular plug (not available with 347V or 480V) <sup>6,7</sup>					LAPZU	360° motion sensor with photocell, pre-wired <sup>6,10</sup>					
	WGX	Standard wire guard, installed					LAMOSZU	360 motion sensor, dimming and switching photocell, pre-wired (T24 compliant) <sup>6,10</sup>					
	<u>Cord sets:</u>						LCMOSZU	Aisle motion sensor, dimming and switching photocell, pre-wired (T24 compliant) <sup>6,10</sup>					
	CS1W	6' white cord with straight-blade plug, 120V <sup>8,9</sup>											
	CS3W	6' white cord with twist-lock plug, 120V <sup>8,9</sup>											
	CS7W	6' white cord with straight-blade plug, 277V <sup>8,9</sup>											
	CS11W	6' white cord with twist-lock plug, 277V <sup>8,9</sup>											
	CS25W	6' white cord with twist-lock plug, 347V <sup>8,9</sup>											
	CS97W	6' white cord with twist-lock plug, 480V <sup>8,9</sup>											
	CS93W	6' white cord, 600V SE00W, no plug (no voltage required) <sup>8</sup>											

Accessories: Order as separate catalog number.											
<u>Mounting:</u>				<u>Wire guards:</u>				<u>Cord sets for IMP option:</u>			
IBAC120 M20	Aircraft cable 10' with hook (one pair)			WGIBE	Wire guard for use with L24 fixtures			CS1WIMP	Straight plug, 120V <sup>8,13</sup>		
IBAC240 M20	Aircraft cable 20' with hook (one pair)			WGIBE4	Wire guard for use with L48 fixtures			CS3WIMP	Twist-lock, 120V <sup>8,13</sup>		
IBHMP	Hook monopoint							CS7WIMP	Straight plug, 277V <sup>8,13</sup>		
ZACVH	Aircraft 10' V hanger (one pair)							CS11WIMP	Twist-lock, 277V <sup>8,13</sup>		
IBLPMP	Pendant monopoint splice box, includes side covers (not available with fixtures utilizing back pack when ordered with 347, 480 & HVOLT) <sup>11</sup>							CS93WIMP	600V 50 white cord, no plug (no voltage required) <sup>8,13</sup>		
IBLPMPBH	Pendant monopoint splice box with 3/4" hub, includes side covers (not available with fixtures utilizing back pack when ordered with 347, 480 & HVOLT) <sup>11</sup>										
HC36	Hanger chain, 36" (one pair)										
THUN	Tong hanger bracket (order 2 per fixture) <sup>12</sup>										

- Notes**
- Not available with OUTCTR option.
  - Visible pixilation is present when choosing L/LENS option. Not recommended for applications where direct viewing of high intensity LED's will be unacceptable.
  - Ships standard with surge protection.
  - Utilizes fixture backpack. 30000LM only for use in ambient temperatures up to 35°C. Not available with IMP option or cord with plug options. Utilizes PS155SCP. Not available with 347 or 480.
  - Ships standard on HVOLT, 347, 480V, and E15WCP and all Motion sensors. Should not be added to the description.
  - Must specify voltage.
  - Must be factory installed. Must have "IMP" power cord to power fixture. Cordsets may be ordered with fixture or as accessory. Not available with E15WCP option. Fixture and cord set ship separately. Example:  
Ordered as:  
IBE L48 18000LM ATC MD 120 GZ10 40K 80CRI CS1WIMP DWH  
Ships as:  
IBE L48 18000LM ATC MD MVOLT GZ10 40K 80CRI IMP DWH CS1WIMP
  - All cord sets are 18/3, 6', white. Additional lengths available 10', 15' and 20'. (ex. CS1WL10)
  - Cord sets are voltage specific. Specify voltage. Other configurations available. Consult factory.
  - Other configurations available, see page four for additional options.
  - Additional support cables required when used with L48.
  - For use in applications with ambient temperatures up to 35°C for 12000LM - 22000LM fixtures, 30°C for 30000LM fixtures. Not for use on fixtures with E15WCP.
  - Fixtures must have IMP option.

# IBE LED High Bay

## IBH/IBE CONVERSION

IBH Existing			IBE Contract Select Offering			Need IBE 18L and 24L in a 2X4 to match existing IBH form factor?	
IBH Nomenclature	Size	UPC	IBE Nomenclature	Size	UPC	IBE Nomenclature	Size
IBH 12L MVOLT	2X2	889804709100	IBE 12LM MVOLT 40K	2X2	191848491010		
IBH 12000LM SD080 MD MVOLT OZ10 50K 80CRI WH	2x2	889804681499	IBE 12LM MVOLT 50K	2x2	191848491096		
IBH 15000LM SD080 MD MVOLT OZ10 40K 80CRI WH	2x2	889804708370	IBE 15LM MVOLT 40K	2x2	191848194133		
IBH 15000LM SD080 MD MVOLT OZ10 50K 80CRI WH	2x2	889804708370	IBE 15LM MVOLT 50K	2x2	191848491058		
IBH 18L MVOLT	2X4	889804710472	IBE 18LM MVOLT 40K	2X2	191848491027	IBE L48 18000LM ATC MD MVOLT GZ10 40K 80CRI DWH	2X4
IBH 18000LM SD080 MD MVOLT OZ10 50K 80CRI WH	2X4	889804711738	IBE 18LM MVOLT 50K	2x2	191848491072	IBE L48 18000LM ATC MD MVOLT GZ10 50K 80CRI DWH	2X4
IBH 24L MVOLT	2X4	889804710335	IBE 22LM MVOLT 40K	2x2	191848491195	IBE L48 22000LM ATC MD MVOLT GZ10 40K 80CRI DWH	2X4
IBH 24000LM SD080 MD MVOLT OZ10 50K 80CRI WH	2X4	889804712032	IBE 22LM MVOLT 50K	2x2	191848491133	IBE L48 22000LM ATC MD MVOLT GZ10 50K 80CRI DWH	2X4

## PHOTOMETRICS

See [www.lithonia.com](http://www.lithonia.com).

### OPERATIONAL DATA

Fixture Length	Lumen Package	Lens Option	40K, 80CRI	50K, 80CRI
L24	12000LM	ATC	11,306	11,652
		SD080	11,377	11,726
		L/LENS	12,267	12,643
	15000LM	ATC	13,967	14,395
		SD080	14,055	14,486
		L/LENS	15,155	15,619
	18000LM	ATC	17,762	18,306
		SD080	17,874	18,422
		L/LENS	19,272	19,863
	22000LM	ATC	21,067	21,712
		SD080	21,200	21,850
		L/LENS	22,859	23,559
L48	18000LM	ATC	18,052	18,605
		SD080	18,166	18,723
		L/LENS	19,587	20,188
	22000LM	ATC	22,564	23,256
		SD080	22,707	23,403
		L/LENS	24,486	25,234
	30000LM	ATC	27,845	28,698
		SD080	28,021	28,880
		L/LENS	30,213	31,139

### LUMENS VS. AMBIENT TEMPERATURE

Ambient °C	Ambient °F	Lumen multiplier
0	32	1.035
10	50	1.021
25	77	1.000
30	86	0.993
35	95	0.986
40	104	0.978
45	113	0.971

### CHARACTERISTICS

Length	Lumen package	Wattage				Dimensions - Inches (centimeters)			Weight with ATC Lens in Carton	Comparable light source
		120V	277V	347V	480V	Length	Width	Depth		
L24	12000LM	83	82	81	81	22 (55.9)	15-1/4 (38.7)	4-3/8 (11.1)	8.2 lbs (3.7 kg)	175W MH, 4-lamp T8 HBF, 2-lamp T5HO
	15000LM	107	105	104	104	22 (55.9)	15-1/4 (38.7)	4-3/8 (11.1)	8.2 lbs (3.7 kg)	200W MH, 6-lamp T8 NBF
	18000LM	137	137	131	132	22 (55.9)	15-1/4 (38.7)	4-3/8 (11.1)	8.2 lbs (3.7 kg)	250W MH, 6-lamp T8 HBF, 4-lamp T5HO
	22000LM	166	165	161	161	22 (55.9)	15-1/4 (38.7)	4-3/8 (11.1)	8.2 lbs (3.7 kg)	400W MH, 6-lamp T5HO
L48	18000LM	136	136	133	133	44 (111.8)	15-1/4 (38.7)	4-3/8 (11.1)	18 lbs (8.2 kg)	250W MH, 6-lamp T8 HBF, 4-lamp T5HO
	22000LM	166	165	161	161	44 (111.8)	15-1/4 (38.7)	4-3/8 (11.1)	18 lbs (8.2 kg)	400W MH, 6-lamp T5HO
	30000LM	215	213	205	204	44 (111.8)	15-1/4 (38.7)	4-3/8 (11.1)	18 lbs (8.2 kg)	575W MH, 10-lamp T8 HBF

### PROJECTED LUMEN MAINTENANCE

Operating hours	0	10,000	20,000	30,000	40,000	50,000	60,000	70,000	80,000	90,000	100,000
Lumen maintenance factor	100%	96%	94%	91%	89%	87%	85%	82%	80%	78%	76%

## LSXR - Fixture Mount Sensor (see [www.sensorswitch.com](http://www.sensorswitch.com) for additional information)

- Four interchangeable lenses.
- Integrated mounting bracket drops lens down 3" from chase nipple.
- Single or dual relay versions — designed with robust protection from the harsh switching requirements of T5 and LED loads.
- Photocell and 0-10VDC dimming options.
- No PIR field calibration or sensitivity adjustments required.
- Not available 208 or 240V.



LSXR configuration	Comparable CMRB sensor	Old style sensor nomenclature
<b>For shortest lead times use one of the following LSXR configurations</b>		
LCOZU	CMRB 50	MSI
LCH0SZU	CMRB 50 D	MSID
LCPZU	CMRB 50 P	MSIPED
LAOZU	CMRB 6	MSI360
LAH0SZU	CMRB 6 D	MSI360D
LAPZU	CMRB 6 P	MSI360PED

### SELECTIONS BELOW WILL EXTEND ORDER LEAD TIME. CONSULT YOUR SALES REPRESENTATIVE FOR DETAILS.

#### SINGLE RELAY

Example: LAH0SZU

##### ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Series	Lens option	Dimming/Photocell	Max. dim Level	Min. dim level	Temp/Humidity	Default time delay
L LSXR passive infrared indoor occupancy sensor	A High mount, 360°	O None <sup>1</sup>	0 10 VDC	5 Minimum dimming level of ballast	Z None	I 30 seconds
	B Low mount, 360°	H High/low occupancy operation	9 9VDC	1 1 VDC	T Low temperature	D 2.5 minutes
	C High mount aisleway	P Switching photocell (on/off)	8 8VDC	2 2 VDC		X 5 minutes
		M Dimming and switching photocell	7 7VDC	3 3 VDC		R 7.5 minutes
		G Dimming and switching photocell with high/low occupancy operation		4 4 VDC		U 10 minutes (with minimum 15 minutes on time)
				5 5 VDC		V 15 minutes
				6 6 VDC		W 20 minutes
						Y 30 minutes

#### DUAL RELAY (Available with 120, 277, and 347V only)

Example: LA2KZU

##### ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Series	Lens option	Poles	Operating mode	Temp/Humidity	Default time delay
L LSXR passive infrared indoor occupancy sensor	A High mount, 360°	2 Dual relay	J None	Z None	I 30 seconds
	B Low mount, 360°		K Alternating off relays (promotes even lamp wear)	T Low temperature	D 2.5 minutes
	C High mount aisleway		O Alternating off relays w/photocell		X 5 minutes
			P Switching photocell (on/off)		R 7.5 minutes
			E Photocell on/off (pole 1 only)		U 10 minutes (with minimum 15 minutes on time)
			F Photocell on/off - both poles (dual set-point)		V 15 minutes
					W 20 minutes
					Y 30 minutes

Example: LENS 50 J100

Replacement lenses: Order as separate catalog number.		
Series	Lens type	Package quantity
Lens	6 High mount 360°	U Unit
	10 Low mount 360°	J10 10-pack
	50 High mount aisleway	J100 100-pack

##### Notes

- 1 Dimming level fields not required when this option is chosen.

## RRL - RELOC®-Ready Luminaire

- RRL connectors can be used with Quick-Flex®, System 820 and OnePass® systems.
- Load side of connector factory installed to luminaire.
- 4-pole mating connector with push-in terminations allows for simple installation.
- Touch-safe design on both halves meets UL/CSA requirement.
- Wiping contact design allows safe disconnect under load.



**ORDERING INFORMATION** Lead times will vary depending on options selected. Consult with your sales representative. **Example: RRLA**

Series	Wiring instructions	
RRL RELOC®-ready luminaire	A Hot conductor wired to position #1 (phase A) B Hot conductor wired to position #2 (phase B)	AE Hot conductor wired to position #1 (phase A), hot conductor #2 wired to position #2 (phase B) <sup>1</sup> C12S Hot conductor in position #1 (phase A), low voltage conductor #1 in position #2, low voltage conductor #2 in position #3 <sup>2</sup>

### Compatible RELOC® Cables for Industrial Luminaires (shipped and ordered separately)



#### Notes

- 1 AE commercial fixtures should disconnect the TSPL before unplugging the RRL so it does not go into discharge mode. Requires fixture to have a battery option.
- 2 C12S option is used with the OnePass for 0-10V/DALI applications

## IMP – Integrated Modular Plug

- The integrated modular plug (IMP) option allows the installer to plug and play.
- Cord sets connect quickly to any fixture with IMP option.

IMP compatible cord sets <sup>1</sup>	
CS1WIMP	Straight plug, 120V
CS3WIMP	Twist-lock, 120V
CS7WIMP	Straight plug, 277V
CS11WIMP	Twist-lock, 277V
CS25WIMP	Twist-lock, 347V
CS93WIMP	600V SE00W white cord, no plug
CS97WIMP	Twist-lock, 480V

#### Notes

- 1 Cord set required for fixture operation. All cord sets are 18/3, 6' white.